



M/T LAMENTIN

**11320 TDW Product/Chemical / LPG Tanker IMO II
Twin Skeg Shallow draft**

Disponent Owner PETROMARINE
26 rue de Campilleau - 33520 BRUGES (FRANCE)
Phone (33) 5 56 16 15 14 - Fax (33) 5 56 16 75 38 - Telex 560828
www.petromarine.fr

GENERAL INFORMATION

July-07

Description	Motor tanker / Two variable pitch propellers / Separated Ballast Tanks / Double hull
Built	2007 by TERSAN SHIPYARD (Turkey)
Flag	French
IMO	9377054
Call Sign	FNKJ
Communications	Phone : 761119856 / Fax : 761119858 Telex : 422800376 E-mail : fnkj@globeemail.com
Class	BV, I * Hull * Mach, Oil Tanker-ESP/Chemical Tanker-ESP Liquified Gas Carrier-LPG ESP - Unrestricted navigation * AUT - UMS AUT - PORT, AVM - DPS, MANOVR, SYS-NQ-1, IG, Clean Ship Super

6 Natural segregations

1P + 1S	=	1420 CBM
2P + 2S	=	1825 CBM
3P + 3S	=	2243 CBM
4P + 4S	=	2245 CBM
5P + 5S	=	1537 CBM
6P + 6S	=	1838 CBM

DIMENSIONS

L.O.A.	119,50 m
L.B.P.	113,40 m
Beam	20,00 m
Depth	9,80 m
GRT / NRT	7292 UMS / 3580 UMS
Parrallel body length (draft 6,50)	59,12 m
KTM	36 m

Cargo tanks at 98% = 11108 CBM

Sloptank at 98%	=	357 CBM
Gas capacity	=	984 CBM
Total at 98%	=	12449 CBM

LOAD LINE DATA

Summer deadweight	11320 mt
Summer draft	7,713 m
Design deadweight	8734 mt
Design draft	6,50 m
Tropical deadweight	11670 mt
Tropical draft	7,87 mt
TPC at summer draft	21.5 mt
Light Weight	3811 mt
Air draft (ballast)	30,60 m

CARGO TANKS/PUMPS

12 main cargo tanks and 2 sloptank epoxy coated
2 LPG tank on deck, type C, 17 bars at 50°C
6 grades segregated
Cargo pipes in stainless steel
Stainless steel heat exchangers on deck up to 65°C
EEC calibrated cargo tanks
Closed loading / Ullaging
12 x 300 CBM/h electric deep-well pumps
IGS/Nitrogen generator system 2 x 850 Nm³/h at 5% oxygen

MACHINERY/SPEED/CONSUMPTION

2 Main engines	MAK 8M25 2 x 2400 kW (IFO380)
Auxiliary engines	YANMAR 3 x 850 kW (IFO 380)
Shaft alternator	2 x 500 kW
Propellers	2 x CP 4 blades
Bow thruster	1 electric 500 kW
Derrick	1 x 5T with an outreach of 4 m
Speed	13,5 kn on 16 mt / day IFO 380 cst
Capacities MT	HFO 360 / GO 60 / FW 130 / LO 20

